



Yabby3

LTE-M / NB-IoT

Compact and ultra-rugged battery-powered GPS asset tracker featuring 10+ years battery life



'Deploy Once' Battery Life

Over 10+ years battery life at once-daily location updates



User-Replaceable Batteries

Uses off-the-shelf 3 x AAA batteries



Adaptive Tracking

Periodic or optional movement-based tracking - tracks assets throughout the day and/or when movement occurs, entering sleep mode when inactive to conserve power and data usage



Battery Life Alerts

"Battery Low" and "Battery Critical" alerts



Ultra-Rugged

Ultra-rugged and weatherproof IP68, IK06 Housing

Connectivity

LTE-M / NB-IoT

Nordic nRF9160 Modem operates on all major global LTE-M and NB-IoT bands.
Supported LTE bands:

(supports roaming between networks - roaming SIM required)

LTE-M (Cat-M1): B1, B2, B3, B4, B5, B8, B12, B13, B14, B17, B18, B19, B20, B25, B26, B28, B66
NB-IoT (Cat-NB1/NB2): B1, B2, B3, B4, B5, B8, B12, B13, B17, B19, B20, B25, B26, B28, B66

SIM Size & Access

Internal Nano 4FF SIM

Batteries

User-Replaceable Batteries

3 x AAA. *Batteries not included.*

Supported Battery Types

*Lithium (LiFeS2) - recommended for best performance

*Please dispose of Lithium batteries in a safe and responsible manner

**Battery Life Estimates

Once Daily location updates - 10+ years
Movement-Based location updates - 3 years
Hourly location updates - 1.5 years

Location

GNSS

Sony CXD5605

Constellation

Concurrent GPS, GLONASS, Galileo, QZSS

Tracking Sensitivity

-147 dBm cold start / -161 dBm hot start

*Location Accuracy

~1m 2D RMS, GPS, -130dBm

GNSS Assistance

GNSS almanac and ephemeris data for greater sensitivity and position accuracy

Low Noise Amplifier

GPS signals are filtered and boosted by a SAW filter and low-noise amplifier (LNA) allowing operation where other units fail

Cell Tower Location

Cell tower location fallback for positioning when GPS can't get a fix

Power

Input Voltage

3-5.5V

Sleep Current

<10uA*
*Average current in lowest power configuration

Mechanics / Design

Dimensions

Standard - 84 x 63 x 24 mm (3.31 x 2.48 x 0.94")
Livestock Collar - 109 x 60 x 30 (4.29 x 2.36 x 1.18")
Snap Housing (Smallest Size, not IP67 rated) - 75 x 45 x 25 mm (2.95 x 1.77 x 0.98")

Weight

80g

Housing

Non-branded housing for optional white-labeling

Mechanics / Design *(continued)*

| | |
|----------------------------|--|
| IP/IK Rating | Ultra-rugged and waterproof IP68 and IK06-rated housing ensures the Yabby3 can withstand impact, fine dust, and brief submersion |
| Installation | Compact and concealable. Multiple installation options for covertly and easily securing the device to assets with screws, bolts, cable ties, rivets, and more. Collar housing available for securing device to livestock. Stainless steel screws supplied. |
| Operating Temperature | -30°C to +60°C |
| Cellular Antenna | Internal |
| GPS Antenna | Internal |
| 3-Axis Accelerometer | 3-Axis Accelerometer to detect movement, high G-force events |
| Diagnostic LED | Diagnostic LED indicates operation status |
| Flash Memory | Store weeks of records if device is out of cellular coverage. Storage capacity for over 2 weeks of 2-minute logging. |
| On-Board Speed and Heading | Current speed and heading is reported with each position update |
| On-Board Temperature | The device reports internal temperature which provides an indication of ambient temperature but may not always be precise |

Smarts

| | |
|-------------------------------------|--|
| Auto-APN | Auto-APN allows the device to analyze the SIM card and select the correct APN details from a list that is pre-loaded in the device's firmware |
| Battery Life Monitoring | "Battery Low" and "Battery Critical" alert levels |
| Geofence Alerts | The server can use device location to create geofences and alerts if an asset enters or leaves designated locations |
| Geofence Download to Device | Geofences can be downloaded directly to the device for enhanced location-based actions and alerts. Maximum of 100 Geofences with up to 100 points per geofence. |
| Impact Detection | Configure impact-detection alerts when G-forces are exceeded by a user-defined threshold |
| Intelligent Power Management | Early registration abort and location scan throttling options |
| Periodic or Movement-Based Tracking | Configure parameters to send updates based on set time intervals or when movement occurs. Adaptive tracking technology detects when the device is on the move and increases the update rate, providing detail when you need it while conserving battery when stationary. |
| Preventative Maintenance | Set reminders based on distance traveled and run hours to reduce maintenance and repair costs |
| Run Hour Monitoring | Capture run hours based on movement to understand and optimize asset utilization |
| Sleep Mode | Stationary devices enter sleep mode until movement occurs to conserve battery life and optimize data usage |
| Theft Recovery | Switch to Recovery Mode in the case of theft or loss to activate real-time tracking for asset retrieval |
| Tip Detection & Rotation Counting | Axis angle reporting, tip detection and rotation counting (planned) |

Device Management

| | |
|----------------------------|---|
| Flexible Configuration | Configure device parameters such as position update rate, movement and accelerometer settings, and more to fit any tracking application |
| Device Management Platform | Manage, monitor, configure, debug, update, and restart devices remotely from our cloud-based device management system |
| Configuration App | Configurable with DMLink Provisioning tool |

Integration

| | |
|-------------------------|-----------------------------|
| Third-Party Integration | TCP Direct or HTTPS Webhook |
|-------------------------|-----------------------------|

Security

| | |
|---------------|---|
| Data Security | Military-level AES-256 Encryption from device to Device Management Platform to protect the integrity and confidentiality of telematics data. Data forwarded to third-party systems is sent via HTTPS for end-to-end security. |
|---------------|---|

Warranty

| | |
|-------------------------|----------------------------------|
| Manufacturer's Warranty | Two-year manufacturer's warranty |
|-------------------------|----------------------------------|

Certifications

| | |
|--|--|
| Please visit support.digitalmatter.com for a full list of compliance specifications and documentation for your region | LTE-M / NB-IoT - FCC, ISED, UKCA, CE, ACMA RCM, EMC, RoHS |
|--|--|

*Positioning accuracy specifications are provided by the GNSS supplier and reflect ideal conditions. Device configuration, installation, environmental conditions, augmentation services, and many other factors may lead to variations in positioning accuracy.

**Battery life estimates are influenced by several factors including temperature, installation and orientation of the device, the frequency of location updates, network coverage, sensor integrations, peripherals, accelerometer settings, and more. Estimated battery life calculators are available at support.digitalmatter.com.